



NOTES:

- FOR THE NON-DISCONNECT ENCLOSURE, THE CUSTOMER HAS TWO CHOICES OF ENCLOSURE MOUNTING. EXTERNAL MOUNTING FEET CAN BE INSTALLED AND MOUNTING DIMENSIONS WILL BE AS SHOWN. IF THE CUSTOMER CHOOSES TO USE INTERNAL MOUNTING, SUBTRACT 1.5 FROM MOUNTING FOOT DIMENSIONS SHOWN. THESE STATEMENTS DO NOT APPLY TO THE DISCONNECT ENCLOSURE PRODUCT.
- THE BASE PRODUCT IS OFFERED IN THE NON-DISCONNECT ENCLOSURE WITH BOLT-ON BREAKERS. AVAILABLE OPTIONS ARE:
 - FORM D - INTERNAL THERMOSTAT
 - FORM T - DISCONNECT ENCLOSURE
 - FORM SA - SURGE ARRESTER
- NON-DISCONNECT ENCLOSURE AVAILABLE IN NEMA 12 & 4, 4X.
- DISCONNECT ENCLOSURE AVAILABLE IN 12 & 4, 4X.
- MAIN BREAKER AND CONTACTOR ARE CHOSEN IN Pairs. EXAMPLE: IF A 150 AMPERE MAIN BREAKER IS NEEDED, A SUITABLE CONTACTOR IS AUTOMATICALLY CHOSEN.

REFERENCE DRAWING

NON-DISCONNECT ENCLOSURE	DISCONNECT ENCLOSURE
GC-0671	GC-0671
GA-1856	GA-1857
GB-0446	GB-0446
GB-0447	GB-0447
	FIELD WIRING (3ø)
	FIELD WIRING (1ø)



DATE	REF:	DATE	REVISION
11/6/95	MS-1 HALL	11/6/95	R1 MANUFACTURE
3/27/96	COMPONENTS	3/27/96	R1 TO FORM T
07/09/03	LUG & BUS	07/09/03	R2 ADD GROUND
04/21/04	CONTRACTOR SHIELD	04/21/04	R3 UPGRADE TO LED LIGHTS, ADD CONTRACTOR SHIELD

DATE	DATE	DATE	DATE
11/7/95	11/7/95	11/7/95	11/7/95
11/7/95	11/7/95	11/7/95	11/7/95
11/7/95	11/7/95	11/7/95	11/7/95

DATE	DATE	DATE	DATE
11/7/95	11/7/95	11/7/95	11/7/95
11/7/95	11/7/95	11/7/95	11/7/95
11/7/95	11/7/95	11/7/95	11/7/95
11/7/95	11/7/95	11/7/95	11/7/95

DATE	DATE	DATE	DATE
11/7/95	11/7/95	11/7/95	11/7/95
11/7/95	11/7/95	11/7/95	11/7/95
11/7/95	11/7/95	11/7/95	11/7/95
11/7/95	11/7/95	11/7/95	11/7/95

CONFIDENTIAL INFORMATION CONTAINED HEREIN IS CONFIDENTIAL. IT IS THE PROPERTY OF NELSON HEAT TRACING SYSTEMS. IT IS TO BE USED SOLELY FOR THE PROJECT AND NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. WITHOUT THE WRITTEN CONSENT OF NELSON HEAT TRACING SYSTEMS.

ASSEMBLY
 AMBIENT CONTROL PANEL 120/208V
 42 CIRCUIT 240VAC, MAX. NEMA 12&4, 4X
 AP42PC CLASS: 305 SC: 1/8"=1" D/L

CONFIDENTIAL PROPERTY OF NELSON HEAT TRACING SYSTEMS
 TULSA, OK, USA FAX (918)222-8308
 PHONE (918)222-8300

GD-0357 R 3