



- NOTES:
1. ALL WIRE TO BE #14 TYPE UNLESS SHOWN OTHERWISE.
 2. TERMINI WITH PRINTED WIRE NUMBERS. OBTAIN THE LIST ON PAGES 28 AND 29.
 3. THE COMPRESSOR OR SHOCK TYPE TERMINAL.
 4. DESIRED WIRING INCLUDE FIELD WIRING.
 5. DESIRED WIRING INCLUDE FIELD WIRING. 11 TO PAUL.
 6. GROUND WIRE SIZE OF TRANSFORMER 11 TO PAUL.
 7. CONNECTIONS IN JUNCTION BOX MUST BE SWITCH-TIGHT. BREAKER TIGHTENING WILL BE PERFORMED BY CONTRACTOR.
 8. GENERAL PRACTICE: ALL WIRING MUST BE SWITCH-TIGHT. BREAKER TIGHTENING WILL BE PERFORMED BY CONTRACTOR.
 9. TO KEEP PROTECT COMPRESSION RATING ENCLOSED, INSTALL CONDUIT TO PROTECT FROM STAIN FROM CONDENSATE.

REFERENCE DRAWING

GD-387
CB-521
GA-2072
GA-2073

ASSEMBLY
FIELD WIRING (30)
DOOR MACHINING
DOOR MACHINING

REV	DATE	BY	DESCRIPTION
1	10/20/72
2	11/20/72
3	12/20/72
4	1/20/73
5	2/20/73
6	3/20/73
7	4/20/73
8	5/20/73
9	6/20/73
10	7/20/73
11	8/20/73
12	9/20/73
13	10/20/73
14	11/20/73
15	12/20/73
16	1/20/74
17	2/20/74
18	3/20/74
19	4/20/74
20	5/20/74
21	6/20/74
22	7/20/74
23	8/20/74
24	9/20/74
25	10/20/74
26	11/20/74
27	12/20/74
28	1/20/75
29	2/20/75
30	3/20/75
31	4/20/75
32	5/20/75
33	6/20/75
34	7/20/75
35	8/20/75
36	9/20/75
37	10/20/75
38	11/20/75
39	12/20/75
40	1/20/76
41	2/20/76
42	3/20/76
43	4/20/76
44	5/20/76
45	6/20/76
46	7/20/76
47	8/20/76
48	9/20/76
49	10/20/76
50	11/20/76
51	12/20/76
52	1/20/77
53	2/20/77
54	3/20/77
55	4/20/77
56	5/20/77
57	6/20/77
58	7/20/77
59	8/20/77
60	9/20/77
61	10/20/77
62	11/20/77
63	12/20/77
64	1/20/78
65	2/20/78
66	3/20/78
67	4/20/78
68	5/20/78
69	6/20/78
70	7/20/78
71	8/20/78
72	9/20/78
73	10/20/78
74	11/20/78
75	12/20/78
76	1/20/79
77	2/20/79
78	3/20/79
79	4/20/79
80	5/20/79
81	6/20/79
82	7/20/79
83	8/20/79
84	9/20/79
85	10/20/79
86	11/20/79
87	12/20/79
88	1/20/80
89	2/20/80
90	3/20/80
91	4/20/80
92	5/20/80
93	6/20/80
94	7/20/80
95	8/20/80
96	9/20/80
97	10/20/80
98	11/20/80
99	12/20/80
100	1/20/81