




GH-M25


The GH-M25 Gland provides a watertight entry into enclosure with minimum IP54 environmental ratings. This fitting is suitable for use with any approved enclosure with a maximum wall thickness of 4.76mm (.188") or with M25 threaded openings. This kit is designed for use with all wattages of Nelson Heat Tracing Systems LT-J, LT-JT and HLT-J heater cables.

KIT CONTENTS

- 1 Cable Gland, .M25 thread
- 1 Conduit Locknut
- 1 Grommet, Heating Cable

APPROVALS:

 II 2 GD EEx e II
 KEMA 03ATEX2020 X

 Ex e II -40°C ≤ Tamb ≤ +55°C
 CSA 1665370 / 1665383



GP-M25

The GP-M25 Gland Fitting provides a watertight entry into enclosure with minimum IP54 environmental ratings. This fitting is suitable for use with any approved enclosure with a maximum wall thickness of 4.76mm (.188") or with M25 threaded openings. This kit is designed for use with cord ranges of 13.0-18.0mm (.512-.709").

KIT CONTENTS

- 1 Cable Gland, .M25 thread
- 1 Conduit Locknut

APPROVALS:

 II 2 G EEx e II



GP-34NPT

The GP-34NPT Gland Fitting provides a watertight entry into Nelson thermostats TA7140 and TH7325 with minimum IP66, IP67 and IP68 environmental ratings. Dual certified Flameproof and Increased Safety, cable gland for use in Zone 1, Zone 2, Zone 21 and Zone 22 hazardous areas with all types of unarmored cable. This kit is designed for use with cord ranges of 11.1-19.9mm (.437-.783").

KIT CONTENTS

- 1 Cable Gland, .3/4" NPT thread

APPROVALS:

 II 2 G D EEx d IIC

 II 2 G D EEx e IIC





GPA-34NPT

The GPA-34NPT Gland Fitting provides a watertight entry into Nelson thermostats TA7140 and TH7325 with minimum IP66, IP67 and IP68 environmental ratings. Dual certified Flameproof and Increased Safety, cable gland for use in Zone 1, Zone 2, Zone 21 and Zone 22 hazardous areas with all types of armored and braided cable. This kit is designed for use with under armor cable diameters ranges of 11.1-19.9mm (.437-.783") with overall cable diameters of 14.0-22.0mm (.551-.876").

KIT CONTENTS

1 Cable Gland, .M25 thread

APPROVALS:

 II 2 G D EEx d IIC
 II 2 G D EEx e IIC

Nelson Heat Tracing Systems products are supplied with a limited warranty. Complete Terms and Conditions may be found on Nelson's website at www.nelsonheaters.com.